

Outdoor Solar Lantern-Fluorescent

The popular hanging lantern design is perfect for camping or emergency lighting. Durable molded plastic is waterproof and self contained with a sealed battery and dual 6 watt lamps. Features a one or two lamp selection switch, 3 watt solar module with cord/plug, 115 VAC adapter and charging LED. Built-in circuitry prevents battery overcharge and over-discharge. Solar panel packaged separately. Models for export (230VAC adapter) available.



Fluorescent Solar Lantern

Model	MSRP
Outdoor Solar Lantern	\$69.00



Motion Sensor

12VDC Motion Sensor- PIR

This passive infrared motion sensor detects heat and movement to activate 12 VDC lighting. Rated for outdoor use in wet locations. Includes sensitivity adjustment to deter false trigger and will allow day or night only operation. Adjustable timer for 1 to 18 minutes, unit is self-resetting during movement. Includes swivel base. UL listed.

Model	Voltage	Max. Load Current	Dimensions	MSRP
PIR-2000/12	12 VDC	10 A	9.0" x 5.5" x 1.6"	\$99.00



SunWize OEM 10 Kit

SunWize[®] OEM and SW Solar Module Kits

SunWize OEM and SW Solar Module kits include a solar module and the SunWize SWIL6 prewired voltage regulator with output cable. The OEM kits are also offered with a fixed tilt, 45° side-of-pole mount. Each kit is also available without the mount. The SWIL6 is mounted in the module junction box. The waterproof controller features a multi-function LED indicator and fuse protection.

SunWize single crystalline, high-efficiency solar modules are manufactured to exceed industry standards providing exceptional reliability and maximum power output. A twenty-year warranty reflects the superior quality and assures long product life. The aluminum side-of-pole mounts include two clamps for nominal 2.5" through 4" poles (OD 2.875" through 4.5"). OEM 5 & 10 kits include a 5 ft. cable, the OEM 20 & 40 and the SW85 & 90 kits include a 10 ft. cable (#12 AWG).

Rated current and voltage at Maximum Power Point (MPP)

Model	Rated Power (Watts)	Rated Voltage (Vmp)	Rated Current (Imp)	Open Circuit Voltage (Voc)	Short Circuit Current (Isc)	Dimensions (inches)	Kit Weight (lbs)	MSRP
OEM5 kit	5	16.4	0.31	20.5	0.38	11.82" x 9.84"	7.0	\$179.00
OEM5 kit without mount							5.75	\$159.00



Solar Path Light

Solar 4-LED Floodlight

Outdoor Dusk to Dawn Solar/LED floodlight features four powerful bright white LED's mounted in a reflective parabolic housing. Wide coverage-use fixture can be aimed in all directions with mounting options of 12" tall ground stake or place atop a wood post or sign. Includes solar panel, 4-AA / 900mAh Ni-Cad batteries. One-year warranty.

Model	Dimensions	Weight (lbs)	MSRP
SL4W	10.0" x 5.5" x3"	2.0	\$135.00